PATENT ABSTRACTS OF JAPAN

(11) Publication number:

2003090210 A

(43) Date of publication of application: 28.03.2003

(51) Int. CI

F01N 3/18

B01D 53/94, F01N 3/02, F01N 3/08,

F01N 3/24, F02D 41/38,

F02D 41/40. F02D 45/00

// B01D 46/42

(21) Application number:

(22) Date of filing:

2001282488

(71) Applicant: MAZDA MOTOR CORP

18.09.2001

(72) Inventor: **KYOGOKU MAKOTO** KAMIOKA TOSHITSUGU

TAIO YOSHINORI

HARADA KOICHIRO

(54) EXHAUST EMISSION CONTROL DEVICE FOR **ENGINE**

(57) Abstract:

PROBLEM TO BE SOLVED: To efficiently regenerate a DPF 9.

SOLUTION: A HC adsorbing catalyst 8 having a catalyst metal supported by a HC adsorbing material is provided in an exhaust passage on the upstream side of the DPF 9. The temperature of the HC adsorbing catalyst 8 is increased so that the catalyst metal has higher activity on condition that the catalyst metal is in an inactive condition or in a low active condition and the HC amount of the HC adsorbing material is determined to be a preset value or more when the regeneration of the DPF 9 is required. The DPF 9 is heated by utilizing heat of oxidizing reaction of HC adsorbed in the HC adsorbing material. COPYRIGHT: (C)2003,JPO

